

View Online at <https://aerobasegroup.com/nsn/5935-00-592-2339>

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.900 inches

Overall Height:

0.710 inches

Overall Width:

0.440 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

3.400 inches

Board Accommodated Length:

2.600 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

500.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Bifurcated accordian leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0