NSN 5935-00-592-4043

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-592-4043

Body Style:
Straight shape, external coupling
Overall Length:
0.983 inches
Overall Height:
1.219 inches
Overall Width:
1.219 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
Between 0.431 inches and 0.441 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16-23 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
22.0 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
270.0
Shell Type:
Hood, top opening
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end all contact groupings
Contact Material:

Contact Surface Treatment:

Copper alloy single mating end all contact groupings

Gold single mating end all contact groupings and silver single mating end all contact groupings

NSN 5935-00-592-4043

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
22 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0