## NSN 5935-00-593-9415

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-593-9415

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.073 inches and 2.103 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 1.847 inches and 1.857 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

25 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

.....

Solid

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Insert Material Specification:** 

Mil-p-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg military specification single material response single mating end

**Included Contact Quantity:** 

25 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-00-593-9415

Mil-std (military Standard):

Mil-p-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.025 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	on
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:	
81349-mil-c-24308/24 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	