# NSN 5935-00-595-9780

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-595-9780
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.009 inches
Overall Height:
1.703 inches
Overall Width:
1.703 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.142 inches and 0.157 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.376 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.376 inches
Distance From Mounting Shoulder To Front Face:
Between 0.442 inches and 0.447 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
24-1 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
345.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

# NSN 5935-00-595-9780

Electrical Receptacle Connector - Page 2 of 2



### **Included Contact Quantity:**

128 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-38999 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.