

View Online at <https://aerobasegroup.com/nsn/5935-00-599-6321>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

0.734 inches

**Overall Diameter:**

0.234 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Brm all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut and externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thread Length:**

0.110 inches

**Thread Size:**

0.190 inches and 0.190 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Copper alloy 360

**Shell Surface Treatment:**

Gold

**Shell Material Specification:**

Qq-b-626, alloy 360 federal specification single material response

**Insert Material Specification:**

L-p-403, type 1 federal specification single material response single mating end

**Included Contact Quantity:**

2 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Special Features:**

Contact designation srm

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf and unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0