Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-599-8368

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 1.198 inches and 1.228 inches
Overall Height:
Between 0.585 inches and 0.660 inches
Overall Width:
Between 0.479 inches and 0.509 inches
Environmental Protection:
Corrosion resistant and shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
Between 0.979 inches and 0.989 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Thread Length:
0.130 inches
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Insert Material: Plastic diallyl phthalate single mating end **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping Shell Material: Steel **Shell Surface Treatment:** Cadmium and chromate **Shell Material Specification:** Qq-s-698 federal specification single material response **Insert Material Specification:** Mil-p-19833, ty gdi-30f military specification single material response single mating end **Included Contact Quantity:** 9 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.009 gold grains, troy and 0.009 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-19833 spec.