## NSN 5935-00-600-2594

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-600-2594 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.031 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Environmental Protection:** Heat resistant and moisture proof and shock resistant and salt water resistant and solvent resistant and vibration proof and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** Between 0.562 inches and 0.593 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16s-1 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 22.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway

0.0

Shell Type:

Solid

**Connector Locking Method:** 

**Insert Position In Deg:** 

Internally threaded coupling ring

## NSN 5935-00-600-2594

Electrical Receptacle Connector - Page 2 of 2



Thread Length:
0.290 inches and 0.375 inches
Thread Size:
1.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and copper single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surf gold
Precious Material:
Gold
Test Data Document:
81349-milc005015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0