

View Online at <https://aerobasegroup.com/nsn/5935-00-601-5469>

Overall Length:

0.730 inches

Overall Height:

Between 1.695 inches and 1.711 inches

Overall Width:

Between 1.695 inches and 1.711 inches

Environmental Protection:

Pressure proof and moisture proof and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.143 inches and 0.153 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.370 inches and 1.380 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.370 inches and 1.380 inches

Distance From Mounting Shoulder To Front Face:

Between 0.635 inches and 0.655 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

24-74 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-367, comp 6061, t6 federal specification single material response

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.074 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-81511/30 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.