Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-603-6376

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling Overall Length:
0.844 inches
Overall Diameter:
1.766 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type: Back shell
Mating End Quantity:
Contact Position Arrangement Style: 24-35 single mating end
Contact Removability:
-
Removable single mating end single contact grouping Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 Shell Turner
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.219 inches
Thread Size: 1.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-00-603-6376

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

Nickel

Included Contact Quantity:

128 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.128 gold grains, troy and 0.128 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-38999 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.