Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-603-9381

ead Class:	
ead Direction:	
nt-hand	
ly Style:	
ight shape w/cable clamp	
erall Length:	
32 inches	
hing Diameter:	
25 inches	
erall Height:	
00 inches	
erall Width:	
00 inches	
ironmental Protection:	
atherproof	
hreaded Mounting Hole Diameter:	
25 inches	
ter To Center Distance Between Mounting Facilities Parallel To Heigh	t:
8 inches	
ance Between Centerlines Of Mounting Facilities Parallel To Body Wi	dth:
8 inches	
ance From Mounting Shoulder To Front Face:	
56 inches	
eaded Device Type:	
pling facility	
ing End Quantity:	
tact Position Arrangement Style:	
ngle mating end	
ntact Removability:	
removable single mating end single contact grouping	
ntact Maximum Ac Voltage Rating In Volts:	
0.0 single mating end single contact grouping	
II Туре:	
d	
nector Locking Method:	
ernally threaded shell	
nector Cable Strain Relief Method:	
npression nut	
lio Frequency Type Contact Characteristic Impedance In Ohms:	

NSN 5935-00-603-9381

Electrical Receptacle Connector - Page 2 of 2



	d Size:
	inches
	nal Location:
Back s	single mating end single contact grouping
	ct Material:
Coppe	er alloy single mating end single contact grouping
Conta	ct Surface Treatment:
Silver	single mating end single contact grouping
Insert	Material:
Plastic	tetrafluoroethylene single mating end
Termi	nal Type:
Solder	well single mating end single contact grouping
Shell	Material:
Coppe	er alloy
Shell	Surface Treatment:
Silver	
Includ	led Contact Quantity:
1 sing	e mating end single contact grouping
Includ	led Contact Type:
Coaxia	al socket single mating end single contact grouping
Precio	ous Material And Location:
Conta	ct and shell surface silver
Precio	ous Material And Weight:
0.105	silver grains, troy
Precio	ous Material:
Silver	
Threa	d Series Designator:
Unef	
Shelf	Life:
N/a	
Unit C	of Measure:
Demil	itarization:
No	
Fiig:	
A039b	0