

View Online at <https://aerobasegroup.com/nsn/5935-00-605-4122>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

0.750 inches

**Overall Diameter:**

0.380 inches

**Environmental Protection:**

Weatherproof

**Cable Entrance Diameter:**

Between 0.075 inches and 0.095 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Dm single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

120.0 and 240.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Compression nut

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver and gold

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact and shell surfaces silver and contact and shell surfaces gold

**Precious Material And Weight:**

0.105 silver grains, troy and 0.105 gold grains, troy

**Precious Material:**

Silver and gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0