## NSN 5935-00-605-6709

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-605-6709

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

Between 4.335 inches and 4.345 inches

**Overall Width:** 

0.980 inches

**Unthreaded Mounting Hole Diameter:** 

0.180 inches

**Distance Between Mounting Facility Centers:** 

4.100 inches

**Board Accommodated Length:** 

1.300 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.071 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Fixed inter-contact

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Wire wrap single mating end single contact grouping

**Insert Material Specification:** 

Mil-p-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

96 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.096 gold grains, troy

## NSN 5935-00-605-6709

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-p-19833 spec.