

View Online at https://aerobasegroup.com/nsn/5935-00-605-6716

Thread Class: 2a Thread Direction: Right-hand Body Style: Rectangular shape, w/jackscrew Overall Length: Between 2.265 inches and 2.285 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.890 inches and 1.910 inches Overall Height: 5.100 inches Overall Width: Between 1.880 inches and 1.910 inches Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization Method:
Thread Direction: Right-hand Body Style: Rectangular shape, w/jackscrew Overall Length: Between 2.265 inches and 2.285 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.890 inches and 1.910 inches Overall Height: 5.100 inches Overall Width: Between 1.080 inches and 1.100 inches Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Right-hand Body Style: Rectangular shape, w/jackscrew Overall Length: Between 2.265 inches and 2.285 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.890 inches and 1.910 inches Overall Height: 5.100 inches Overall Width: Between 1.080 inches and 1.100 inches Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Body Style: Rectangular shape, w/jackscrew Overall Length: Between 2.265 inches and 2.285 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.890 inches and 1.910 inches Overall Height: 5.100 inches Overall Width: Between 1.080 inches and 1.100 inches Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Rectangular shape, w/jackscrew Overall Length: Between 2.265 inches and 2.285 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.890 inches and 1.910 inches Overall Height: 5.100 inches Overall Width: Between 1.080 inches and 1.100 inches Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Overall Length:Between 2.265 inches and 2.285 inchesCenter To Center Distance Between Mounting Facilities Parallel To Length:Between 1.890 inches and 1.910 inchesOverall Height:5.100 inchesOverall Width:Between 1.080 inches and 1.100 inchesEnvironmental Protection:Thermal shock resistantUnthreaded Mounting Hole Diameter:0.149 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:Between 0.540 inches and 0.560 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:52 single mating endPolarization Method:Polarization boss
Between 2.265 inches and 2.285 inchesCenter To Center Distance Between Mounting Facilities Parallel To Length:Between 1.890 inches and 1.910 inchesOverall Height:5.100 inchesOverall Width:Between 1.080 inches and 1.100 inchesEnvironmental Protection:Thermal shock resistantUnthreaded Mounting Hole Diameter:0.149 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:Between 0.540 inches and 0.560 inchesThreaded Device Type:Coupling facilityMating End Quantity:12< single mating endPolarization Method:Polarization boss
Center To Center Distance Between Mounting Facilities Parallel To Length:Between 1.890 inches and 1.910 inchesOverall Height:5.100 inchesOverall Width:Between 1.080 inches and 1.100 inchesEnvironmental Protection:Thermal shock resistantUnthreaded Mounting Hole Diameter:0.149 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:Between 0.540 inches and 0.560 inchesThreaded Device Type:Coupling facilityMating End Quantity:152 single mating endPolarization Method:Polarization Doss
Between 1.890 inches and 1.910 inchesOverall Height:5.100 inchesOverall Width:Between 1.080 inches and 1.100 inchesEnvironmental Protection:Thermal shock resistantUnthreaded Mounting Hole Diameter:0.149 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:Between 0.540 inches and 0.560 inchesThreaded Device Type:Coupling facilityMating End Quantity:152 single mating endPolarization Method:Polarization boss
Overall Height:5.100 inchesOverall Width:Between 1.080 inches and 1.100 inchesEnvironmental Protection:Thermal shock resistantUnthreaded Mounting Hole Diameter:0.149 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:Between 0.540 inches and 0.560 inchesThreaded Device Type:Coupling facilityMating End Quantity:152 single mating endPolarization Method:Polarization boss
5.100 inches Overall Width: Between 1.080 inches and 1.100 inches Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Overall Width:Between 1.080 inches and 1.100 inchesEnvironmental Protection:Thermal shock resistantUnthreaded Mounting Hole Diameter:0.149 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:Between 0.540 inches and 0.560 inchesThreaded Device Type:Coupling facilityMating End Quantity:12Single mating endPolarization Method:Polarization boss
Between 1.080 inches and 1.100 inches Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Environmental Protection: Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Thermal shock resistant Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Unthreaded Mounting Hole Diameter: 0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
0.149 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 1 Contact Position Arrangement Style: 52 single mating end Polarization Method:
Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Between 0.540 inches and 0.560 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
Mating End Quantity: 1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
1 Contact Position Arrangement Style: 52 single mating end Polarization Method: Polarization boss
52 single mating end Polarization Method: Polarization boss
Polarization Method: Polarization boss
Polarization boss
Connector Locking Method:
jj
Jackscrew
Operating Tempurature Rating:
Between -54.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Thread Series Designator:



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.