

View Online at <https://aerobasegroup.com/nsn/5935-00-605-6742>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, external coupling

Overall Length:

Between 0.713 inches and 0.733 inches

Overall Diameter:

Between 0.302 inches and 0.322 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36 and 36

Thread Size:

0.250 inches and 0.250 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 h federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Material Specification:

Qq-s-764, cond a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Contact designation sma

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.