NSN 5935-00-606-8124

Electrical Plug Connector - Page 1 of 2



10.11 C.I.II.10 at III.po.11/aciosacog/oup.co.11/11011/2000 at C.L.	
Thread Class:	
2b	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, internal coupling	
Overall Length:	
Between 0.750 inches and 0.760 inches	
Overall Diameter:	
Between 0.295 inches and 0.305 inches	
Cable Entrance Diameter:	
0.132 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
600.0 single mating end single contact grouping	
Shell Type:	
Solid	
Connector Locking Method:	
Internally threaded coupling nut	
Radio Frequency Type Contact Characteristic Impedance In Ohms:	
93.0 single mating end single contact grouping	
Thread Size:	
0.250 inches	
Contact Material:	
Silver single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and silver single mating end single contact grouping	
Insert Material:	
Plastic single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Copper alloy	
Shell Surface Treatment:	
Silver	
Shell Material Specification:	

Qq-b-626, comp 22 federal specification single material response

NSN 5935-00-606-8124

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0