## NSN 5935-00-606-8924

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-606-8924

Overall Length:
1.000 inches
Overall Diameter:
1.750 inches
Environmental Protection:
Pressure proof
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
35.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
150.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
200.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
180.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded shell
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Tin single mating end single contact grouping
Insert Material:
Ceramic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Material Specification:
Fed standard 66, comp 1345 federal standard single material response

## NSN 5935-00-606-8924

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:**

3 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0