Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-607-9493

Inread Class. 2b Thread Direction: Right-hand Overall Longth: Between 1.600 inches and 1.640 inches Overall Height: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.480 inches and 0.520 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aduminum alloy Surface Treatment: Anodize Straight type wicable clamp Surface Treatment: Anodized Thread Size Unef Surface Treatment: Anodized Thread Size Designator: Unef Surface Treatment: Anodized Thread Size Designator: Na Duril (Inf Measure: To Demilitarization: No Fig: Anolitod	Thread Class:		
Tread Direction: Right-hand Overall Length: Between 1.600 inches and 1.640 inches Overall Height: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.480 inches and 0.520 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Atuminum alloy Syle Designator: Strade Treatment: Anodize Stradestreatment: Anodized Surface Treatment: Anodized Strade Treatment: Anodized Bettiff: Na Bettiff: Na			
Right-hand Overall Length: Between 1.600 inches and 1.640 inches Overall Height: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.480 inches and 0.520 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Stratight type w/cable clamp Stration: Infer Munit Of Measure: Na Material: Aluminum alloy Surface Treatment: Anodize Stratight type w/cable clamp Surface Treatment: Anodized Thread Straties Designator: Inter Of Measure: Na Unit Of Measure: Tau Partilitarization: Na Strate State St			
Overall Length: Between 1.600 inches and 1.640 inches Overall Height: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.480 inches and 0.520 inches Cable Opening Quantity: T Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Straight type w/cable clamp Surface Treatment: Anodized Thread Series Designator: Nandized Thread Series Designator: Nandized Thread Series Designator: Nandized Thread Series Designator: Nandized Thread Series Designator: Na Unit of Measure: Na The Materia Series Designator: Na Series Designator: Na Series Designator: Series Designator: <t< th=""><th></th><th></th><th></th></t<>			
Between 1.600 inches and 1.640 inches Overall Height: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.480 inches and 0.520 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Stright type w/cable clamp Stright type w/cable clamp Inread Stries Naterial: Anodized Stright type w/cable clamp Stright type w/cable clamp Inread Stries Naidized Thread Stries Designator: Inread Stries Designator: Naidized Thread Stries Designator: Naidized Thread Stries Designator: Int of Measure: Naidized Distright of Measure: Int Stries Designator: Naidized Distright of Measure:<			
Overall Height:Between 1.040 inches and 1.080 inchesCable Opening Diameter:Between 0.480 inches and 0.520 inchesCable Opening Quantity:Cable Opening Quantity:1Between 0.480 inches and 0.520 inchesCable Opening Quantity:1Between 0.480 inches and 0.520 inchesBetween 0.480 inches and 0.520 inchesCable Opening Quantity:1Between 0.480 inches and 0.520 inchesBetween 0.480 inches and 0.520 inchesBetween 0.480 inches and 0.520 inches1Between 0.480 inches and 0.520 inches11Between 0.480 inchesAnodizeStraight type w/cable clampStraight type w/cable clampBettifie:NaChesters:Interd Streis Designator:Interd Streis D			
Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.480 inches and 0.520 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aluminum alloy Style Designator: Straiget type wicable clamp Surface Treatment: Anodized Thread Series Designator: Unef Sheft Life: N/a Dit of Measure: No Fig:		35	
Cable Opening Diameter: Between 0.480 inches and 0.520 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aluminum alloy Style Designator: Anodize Straight type w/cable clamp Straight type w/cable clamp Hored Series Designator: Ined Yand Anodized Thread Series Designator: Ined Material: Anodized Thread Series Designator: Ined Thread Series Designator: Ined Material: No Poinilitarization: No Fig:	-		
Between 0.480 inches and 0.520 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Straight type w/cable clamp Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: Na Dint of Measure: - Pomilitarization: No Fig:		35	
Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Straight type w/cable clamp Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: Na Unef Shelf Life: Na Diried Measure: Init of Measure: Init of Measure: Init of Measure: Fig:			
1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Stright type w/cable clamp Striaght type w/cable clamp Anodized Thread Series Designator: Unef Shelf Life: N/a Dit of Measure: r Demilitarization: No Fig:		35	
Size Designation:16Mounting Facility Type And Quantity:1 threaded couplingThread Size:1.125 inchesMaterial:1.125 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStright type w/cable clampSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aDit of Measure:mit of Measure:NoFig:NoFig:			
16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/cable clamp Motized Thread Series Designator: Unef Shelf Life: N/a Unef Shelf Life: N/a Dimitarization: Image: No Fig:			
Mounting Facility Type And Quantity:1 threaded couplingThread Size:1.125 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight type w/cable clampSurface Treatment:AnodizedInterded Series Designator:UnefShelf Life:NaDir of Measure:-Image: Image:			
I thread Size: I.125 inches I.1			
Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/cable clamp Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:		y:	
1.125 inches Material: Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/cable clamp Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demiltarization: No Fig:			
Material:Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight type w/cable clampSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:			
Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/cable clamp Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:			
Surface Treatment:AnodizeStyle Designator:Straight type w/cable clampSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:			
AnodizeStyle Designator:Straight type w/cable clampSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:			
Style Designator:Straight type w/cable clampSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:			
Straight type w/cable clamp Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Surface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:			
Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Pomilitarization: No			
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:			
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-		
N/a Unit Of Measure: Demilitarization: No Fiig:			
Unit Of Measure: Demilitarization: No Fiig:			
 Demilitarization: No Fiig:			
No Fiig:	Unit Of Measure:		
No Fiig:	 Domilitorization		
Fiig:			
ΑΙΟΙΟΟ			
	A10100		