## NSN 5935-00-608-5621

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-608-5621 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and left-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.542 inches **Overall Diameter:** 1.500 inches **Environmental Protection:** Explosion proof and salt water resistant and vibration proof **Distance From Mounting Shoulder To Front Face:** 0.636 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 and 18 **Thread Size:** 

1.375 inches and 1.250 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-00-608-5621

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mount
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.009 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Double stub and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0