NSN 5935-00-608-6433

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-608-6433 **Body Style:** Straight shape, external coupling **Overall Length:** 0.753 inches **Overall Height:** 0.500 inches **Overall Width:** 0.500 inches **Unthreaded Mounting Hole Diameter:** 0.102 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.340 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 0.340 inches **Distance From Mounting Shoulder To Front Face:** 0.378 inches **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Frequency Rating:** 12400.0 megahertz single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Friction **Connector Cable Strain Relief Method:** Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:**

Back single mating end single contact grouping

0 0

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Steel comp 303

NSN 5935-00-608-6433

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shell Material Specification:
Aisi 303 assn standard single material response
Included Contact Quantity:
1 single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0