NSN 5935-00-609-6614



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-609-6614 **Body Style:** Straight shape, external coupling **Overall Length:** 3.125 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Environmental Protection:** Explosion proof **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.317 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.317 inches **Distance From Mounting Shoulder To Front Face:** 0.972 inches **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 20.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 480.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:**

90.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-00-609-6614

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|--------------------------------------------------------|
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 7 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Special Features: |
| Back box 2-1/8in. By 6-1/4 in. By 3-1/2 in. Furnished |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0