# NSN 5935-00-613-4451

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-613-4451 **Body Style:** Rectangular shape **Overall Length:** 2.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.375 inches **Overall Height:** 1.094 inches **Overall Width:** 1.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.745 inches and 0.755 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 28 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Screw **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold and nickel single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1, grade c, cl 1 military specification 1st treatment response single mating end all contact groupings **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum

Cadmium

**Shell Surface Treatment:** 

# NSN 5935-00-613-4451

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14, ty sdi-5 military specification single material response single mating end

## **Included Contact Quantity:**

8 single mating end 1st contact grouping

## **Included Contact Type:**

Round pin single mating end all contact groupings

**Special Features:** 

Furnished items - bracket

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.028 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.