NSN 5935-00-614-0508

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-614-0508

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
2.438 inches
Overall Diameter:
2.719 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
44-1 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Thready Qty Per Inch (tpi):
6 and 8
Thread Size:
2.500 inches and 2.750 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper single mating end all contact groupings or copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and copper single mating end all contact groupings
Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-00-614-0508Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromium
Insert Material Specification:
Mil-m-14 ty mdg military specification single material response single mating end
Included Contact Quantity:
6 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.186 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.