

View Online at <https://aerobasegroup.com/nsn/5935-00-614-0510>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

2.115 inches

Overall Diameter:

2.219 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

32-13 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

41.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

80.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Thread Length:

0.438 inches

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.750 inches and 2.000 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Insert Material Specification:

Mil-m-14, type mdg military specification single material response single mating end

Included Contact Quantity:

5 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.043 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.