NSN 5935-00-615-2235

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-2235 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.344 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Environmental Protection:** Pressure proof **Unthreaded Mounting Hole Diameter:** 0.147 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** B4s single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:**

18

Externally threaded shell Thready Qty Per Inch (tpi):

NSN 5935-00-615-2235

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.750 inches
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0