NSN 5935-00-615-3884

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-3884 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.672 inches **Overall Diameter:** 1.125 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** B4s single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 27 **Thread Size:** 0.812 inches **Terminal Location:** Back single mating end single contact grouping

Back single mating e
Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

NSN 5935-00-615-3884

Insert Material:

Electrical Receptacle Connector - Page 2 of 2



Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Chromate
Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
•
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.004 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0