

View Online at <https://aerobasegroup.com/nsn/5935-00-615-4369>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

3.185 inches

**Overall Height:**

0.660 inches

**Overall Width:**

0.343 inches

**Environmental Protection:**

Moisture proof and vibration proof and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.142 inches

**Distance Between Mounting Facility Centers:**

2.937 inches

**Board Accommodated Length:**

2.504 inches single board

**Board Accommodated Width:**

0.082 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bridged contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end all contact groupings

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end all contact groupings

**Included Contact Quantity:**

15 single mating end all contact groupings

**Included Contact Type:**

Spring pincers single mating end all contact groupings

**Special Features:**

Polarizing key n

**Precious Material And Location:**

Contact surf gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0