NSN 5935-00-615-4369

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-4369

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.185 inches

Overall Height:

0.660 inches

Overall Width:

0.343 inches

Environmental Protection:

Moisture proof and vibration proof and vibration resistant

Unthreaded Mounting Hole Diameter:

0.142 inches

Distance Between Mounting Facility Centers:

2.937 inches

Board Accommodated Length:

2.504 inches single board

Board Accommodated Width:

0.082 inches

Mating End Quantity:

VIC

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end all contact groupings

Included Contact Quantity:

15 single mating end all contact groupings

NSN 5935-00-615-4369

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Spring pincers single mating end all contact groupings
Special Features:
Polarizing key n
Precious Material And Location:
Contact surf gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0