Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-4373

Body Style:
Straight shape
Overall Length:
2.496 inches
Overall Height:
1.136 inches
Overall Width:
0.922 inches
Unthreaded Mounting Hole Diameter:
0.116 inches
Distance Between Mounting Facility Centers:
2.125 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
800.0 single mating end single contact grouping
Polarization Method:
Shell
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:

Terminal Type:

Tab, solder lug single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Insert Material Specification:
Mil-m-14, ty sdg military specification single material response single mating end
Shell Guide Type And Location Designator:
A pin and f pin and 4 pin and 5 pin
Included Contact Quantity:
16 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.016 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.