## NSN 5935-00-615-5337

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-5337 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 2.061 inches and 2.091 inches **Overall Width:** Between 0.359 inches and 0.391 inches **Distance Between Mounting Facility Centers:** Between 1.636 inches and 1.640 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.125 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end **Criticality Code Justification:** Feat **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type mfe military specification single material response single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 

meradea contact Quantity.

8 single mating end single contact grouping

## NSN 5935-00-615-5337

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type
-----------------------

Round pin single mating end single contact grouping

## **Special Features:**

Polarizing pins located to the left of pin a and to the right of pin j; jackscrew type-male and location-right handandjackscrew type-male and location-left hand

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.