

View Online at <https://aerobasegroup.com/nsn/5935-00-615-7405>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and left-hand

**Body Style:**

Straight shape, internal coupling w/backshell

**Overall Length:**

1.316 inches

**Overall Diameter:**

0.729 inches

**Environmental Protection:**

Moisture resistant

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

8-4 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

2300.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Thready Qty Per Inch (tpi):**

28 and 5

**Thread Size:**

0.500 inches and 0.500 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and iridium

**Insert Material Specification:**

Mil-c-5015 military specification single material response single mating end

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold and contact surface silver and shell surface iridium

**Precious Material And Weight:**

0.004 gold grains, troy and 0.004 silver grains, troy and 0.100 iridium grains, troy

**Precious Material:**

Gold and silver and iridium

**Thread Series Designator:**

Unef and double stub

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-5015 spec.