NSN 5935-00-615-7794

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-615-7794 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.719 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Environmental Protection:** Moisture resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.109 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Distance From Mounting Shoulder To Front Face:** 0.812 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 135.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

NSN 5935-00-615-7794

No

Electrical Receptacle Connector - Page 2 of 3



Connector Locking Method:
Externally threaded shell
Thread Length:
0.500 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate and cadmium
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.010 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5935-00-615-7794

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.