

View Online at <https://aerobasegroup.com/nsn/5935-00-615-7833>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

2.234 inches

Overall Height:

2.594 inches

Overall Width:

1.625 inches

Environmental Protection:

Weatherproof

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring and externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.250 inches and 1.250 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surface gold and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.