## NSN 5935-00-615-7851

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-7851

**Body Style:** 

Straight shape

**Overall Length:** 

Between 3.271 inches and 3.291 inches

**Overall Height:** 

1.125 inches

Overall Width:

Between 1.220 inches and 1.240 inches

**Environmental Protection:** 

Vibration resistant

**Distance Between Mounting Facility Centers:** 

Between 2.466 inches and 2.470 inches

**Threaded Device Type:** 

Mounting stud

**Mating End Quantity:** 

1

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Polarization Method:** 

Contact

**Connector Locking Method:** 

Screw

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:** 

Plastic epoxy single mating end

**Contact Surface Treatment Specification:** 

Qq-s-365, type 2, grade b federal specification 1st treatment response single mating end all contact groupings and mil-g-45204, type 1, class

1 military specification 2nd treatment response single mating end all contact groupings

**Terminal Type:** 

Threaded stud single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530, h federal specification single material response single mating end all contact groupings

**Insert Material Specification:** 

Mil-p-18177, type gee military specification single material response single mating end

**Included Contact Quantity:** 

6 single mating end 2nd contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

## NSN 5935-00-615-7851

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:	
0.007 gold grains, troy and 0.007 silver grains, troy	
Precious Material:	
Gold and silver	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	

Mil-std (military Standard):

Mil-g-45204 spec.