NSN 5935-00-615-8949

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-8949 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 3.031 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Unthreaded Mounting Hole Diameter:** 0.147 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** 0.812 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 28-15 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-615-8949 Electrical Receptacle Connector - Page 2 of 2



Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
35 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Data:
81349-mil-c-5015 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0