## NSN 5935-00-615-9293

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-9293 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Hood, top opening w/clamp **Overall Length:** 2.590 inches **Overall Height:** 2.156 inches **Overall Width:** 0.810 inches **Environmental Protection:** Corrosion resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, top opening **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp **Cable Opening Length:** 0.440 inches **Cable Opening Width:** 0.590 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.138 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-00-615-9293

Electrical Plug Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Qq-m-151 federal specification single treatment response
Shell Material Specification:
Qq-a-318 federal specification single material response
Insert Material Specification:
Mil-p-19833, type gdi-30 military specification all material responses single mating end
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.