NSN 5935-00-615-9309

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-615-9309

| Body Style: Straight shape, rectangular Overall Length: 2.906 inches Overall Height: 0.688 inches Overall Width: 1.406 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: 2.469 inches |
|---|
| Overall Length: 2.906 inches Overall Height: 0.688 inches Overall Width: 1.406 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: |
| 2.906 inches Overall Height: 0.688 inches Overall Width: 1.406 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: |
| Overall Height: 0.688 inches Overall Width: 1.406 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: |
| 0.688 inches Overall Width: 1.406 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: |
| Overall Width: 1.406 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: |
| 1.406 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: |
| Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Mounting Facility Centers: |
| 0.188 inches Distance Between Mounting Facility Centers: |
| Distance Between Mounting Facility Centers: |
| |
| 2.469 inches |
| |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 18 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 10.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 730.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Contact Surface Treatment Specification: |
| Qq-s-365 federal specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |

NSN 5935-00-615-9309

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|---|
| Lacquer |
| Included Contact Quantity: |
| 18 single mating end single contact grouping |
| Included Contact Type: |
| Leaf spring single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.018 silver grains, troy |
| Precious Material: |
| Silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |