Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-617-8506

Body Style:
Straight shape
Overall Length:
Between 1.640 inches and 1.680 inches
Overall Height:
Between 1.100 inches and 1.400 inches
Overall Width:
Between 2.290 inches and 2.330 inches
Environmental Protection:
Moisture resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.745 inches and 0.755 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.057 inches and 2.067 inches
Distance From Mounting Shoulder To Front Face:
Between 0.730 inches and 0.770 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16c3 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
5.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
875.0 single mating end 3rd contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1400.0 single mating end 1st contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Radio Frequency Type Contact Characteristic Impedance In Ohms:
73.0 single mating end all contact groupings
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Cold single mating and all contact groupings and silver single mating and all contact groupings

Gold single mating end all contact groupings and silver single mating end all contact groupings

## NSN 5935-00-617-8506

Electrical Receptacle Connector - Page 2 of 2



Plastic sing	le mating end
Terminal T	-
	e mating end 3rd contact grouping
Shell Mater	rial:
Aluminum a	alloy
Shell Surfa	ace Treatment:
Cadmium	
Shell Surfa	ace Treatment Specification:
Qq-p-416,	type 2, cl b federal specification single treatment response
Insert Mate	erial Specification:
Mil-p-14, ty	pe mme military specification single material response single mating end
Included C	contact Quantity:
9 single ma	ting end 2nd contact grouping
Included C	contact Type:
Round sock	ket single mating end all contact groupings
Precious N	laterial And Location:
Contact sur	faces gold and contact surfaces silver
Precious N	laterial And Weight:
0.016 gold	grains, troy and 0.016 silver grains, troy
Precious N	laterial:
Gold and si	lver
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A039b0	
Mil-std (mi	litary Standard):
Mil-p-14 sp	ec.