

View Online at <https://aerobasegroup.com/nsn/5935-00-620-8387>

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

0.609 inches

**Overall Height:**

0.531 inches

**Overall Diameter:**

0.312 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Shrinkable tubing

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

75.0 single mating end single contact grouping

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Copper single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, ty ii military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Copper and gold

**Shell Surface Treatment Specification:**

Mil-g-45204, ty ii military specification 2nd treatment response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold

**Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.