

View Online at https://aerobasegroup.com/nsn/5935-00-622-2895

| Thr | ead Class: |
|------|--|
| 2b | |
| Thr | ead Direction: |
| Rig | nt-hand |
| Ove | erall Width: |
| Bet | ween 0.792 inches and 0.832 inches |
| Boo | ly Angle In Deg: |
| 90.0 | |
| Cab | ole Opening Diameter: |
| Bet | ween 0.187 inches and 0.286 inches |
| Dis | tance From Centerline To Connector End: |
| 1.18 | 33 inches |
| Dis | tance From Centerline To Cable End: |
| 0.80 | 05 inches |
| Cat | ole Opening Quantity: |
| 1 | |
| Siz | e Designation: |
| 10 | |
| Мо | unting Facility Type And Quantity: |
| 1 th | readed coupling |
| Thr | eady Qty Per Inch (tpi): |
| 24 | |
| Thr | ead Size: |
| 0.62 | 25 inches |
| Mat | erial: |
| Alu | ninum alloy |
| Mat | erial: |
| Alu | ninum alloy |
| Sur | face Treatment: |
| Cad | lmium |
| Sty | le Designator: |
| Cla | mp, angle tie strap type |
| Sur | face Treatment: |
| Cad | lmium |
| Tes | t Data Document: |
| 813 | 49-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| forn | nat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| env | ironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thr | ead Series Designator: |
| Une | af standard and a standard and a standard a s |
| Spe | ecification Data: |
| 969 | 06-ms3418 government standard |
| She | elf Life: |
| N/a | |

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A10100

Mil-std (military Standard):

Mil-c-5015 spec.