

View Online at <https://aerobasegroup.com/nsn/5935-00-622-2922>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling w/backshell

**Overall Length:**

2.125 inches

**Overall Height:**

Between 1.469 inches and 1.531 inches

**Overall Width:**

Between 1.469 inches and 1.531 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.156 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.750 inches and 0.781 inches

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-18 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

41.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.290 inches and 0.625 inches

**Thread Size:**

1.188 inches and 1.250 inches

**Terminal Location:**

Back single mating end all contact groupings

**Insert Material:**

Plastic silicone single mating end

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

6 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Special Features:**

In order to complete the connector assembly, the user must obtain/provide the backshell. Standard versions may be ordered as nsn 5935-01-183-6491, p/n m85049/52-1-20w for the straight style, or nsn 5935-01-186-5610, p/n m85049/51-1-20w for the right angle style.

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef and unef

**Specification Data:**

81349-mil-c-5015 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-5015 spec.