# NSN 5935-00-623-8095

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-623-8095 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.427 inches **Overall Diameter:** 0.250 inches **Environmental Protection:** Moisture resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Tnc all mating ends **Contact Removability:** Removable all mating ends single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 32 Thread Size: 0.190 inches **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Plastic polytetrafluoroethylene all mating ends **Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

**Shell Material:** Copper alloy

**Shell Surface Treatment:** 

Silver

# NSN 5935-00-623-8095

Connector Adapter - Page 2 of 2



# **Shell Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response

# **Shell Material Specification:**

Qq-b-626, comp 22 federal specification single material response

# **Included Contact Quantity:**

1 all mating ends single contact grouping

# **Included Contact Type:**

Coaxial socket all mating ends single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and body surface silver

#### **Precious Material And Weight:**

0.010 gold grains, troy and 0.100 silver grains, troy

#### **Precious Material:**

Gold and silver

#### **Thread Series Designator:**

Unf

#### **Shelf Life:**

N/a

#### **Unit Of Measure:**

\_

#### Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.