## NSN 5935-00-623-8256

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-623-8256

**Body Style:**Rectangular shape

**Overall Length:** 

2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches

**Overall Height:** 

0.656 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.219 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

41 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

700.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

980.0 single mating end single contact grouping

Shell Type:

Solid

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

**Shell Surface Treatment:** 

Anodize

**Included Contact Quantity:** 

41 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-00-623-8256

Electrical Receptacle Connector - Page 2 of 2



Precious M	lateriai <i>P</i>	∖nd Lo	cation
------------	-------------------	--------	--------

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.041 gold grains, troy and 0.041 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0