# NSN 5935-00-624-9270

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-624-9270

Body Style:
Straight shape
Overall Length:
0.891 inches
Overall Height:
3.110 inches
Overall Width:
3.860 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.930 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
4
Contact Position Arrangement Style:
C2 1st mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 4th mating end 2nd contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 1 cl 2 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy a380.0
Shell Surface Treatment:

Cadmium

# NSN 5935-00-624-9270

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Shell Material Specification:**

Qq-a-591 alloy a380 federal specification single material response

# **Insert Material Specification:**

Mil-m-19833 ty gdi-30f military specification single material response single mating end

### **Special Features:**

Polarized at position 01 and floating eyelets and tabs

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.109 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.