Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-624-9305

ad Class:
ad Direction:
t-hand and right-hand
y Style:
ght shape, external coupling
all Length:
1 inches
all Height:
1 inches
all Width:
1 inches
readed Mounting Hole Diameter:
) inches
er To Center Distance Between Mounting Facilities Parallel To Height:
) inches
ance Between Centerlines Of Mounting Facilities Parallel To Body Width
) inches
ance From Mounting Shoulder To Front Face:
5 inches
aded Device Type:
shell and coupling facility
ng End Quantity:
act Position Arrangement Style:
7 single mating end
act Removability:
ovable single mating end single contact grouping
act Maximum Current Rating In Amps:
) single mating end single contact grouping
rization Method:
vay or multiple keyway
rt Position In Deg:
I Туре:
nector Locking Method:
mally threaded shell
ady Qty Per Inch (tpi):
ad Size:
5 inches and 2.000 inches

NSN 5935-00-624-9305

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Glass single mating end and plastic polyamide single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.020 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Un and uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0