

View Online at <https://aerobasegroup.com/nsn/5935-00-626-2310>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, internal coupling

**Overall Length:**

2.281 inches

**Overall Height:**

1.780 inches

**Overall Diameter:**

1.719 inches

**Environmental Protection:**

Salt water resistant and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

41.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end all contact groupings

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Potting type

**Thread Size:**

1.500 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper single mating end all contact groupings or copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

2 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.032 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0