NSN 5935-00-626-3182

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-626-3182

Body Style:

Multiple card type

Overall Length:

Between 9.910 inches and 9.950 inches

Overall Height:

0.850 inches

Overall Width:

0.490 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Mounting Facility Centers:

Between 9.535 inches and 9.565 inches

Board Accommodated Length:

4.700 inches second board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

2 rows of independent contacts inserted board all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

5.0 all mating ends all contact groupings

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends

Terminal Type:

Solder well all mating ends all contact groupings

Insert Material Specification:

Mil-g-19833 ty gdi 30 military specification single material response all mating ends

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.086 gold grains, troy

NSN 5935-00-626-3182

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-19833 spec.