

View Online at https://aerobasegroup.com/nsn/5935-00-626-3336

Body Material:
Plastic
Body Style:
Top or bottom mount w/molded saddle
Fabrication Method:
Molded
Tempurature Rating:
-65.0 degrees celsius and 125.0 degrees celsius
Overall Height:
0.972 inches
Overall Width:
Between 1.235 inches and 1.265 inches
Mounting Hole Diameter:
Between 0.213 inches and 0.223 inches
Body Mounting Hole Accommodation Diameter:
Between 1.213 inches and 1.223 inches
Distance Between Mounting Facility Centers:
Between 1.557 inches and 1.567 inches
Mounting Hole Style:
Round, w/two mounting holes
Contact Maximum Current Rating In Amps:
13.0
Contact Material:
Phosphor bronze
•
Contact Surface Treatment:
Contact Surface Treatment:
Contact Surface Treatment: Gold and silver
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity:
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type:
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface:
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: Between 0.140 inches and 0.166 inches
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: Between 0.140 inches and 0.166 inches Mounting Method:
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: Between 0.140 inches and 0.166 inches Mounting Method: Unthreaded hole
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: Between 0.140 inches and 0.166 inches Mounting Method: Unthreaded hole Mounting Type For Which Designed:
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: Between 0.140 inches and 0.166 inches Between 0.140 inches and 0.166 inches Mounting Method: Unthreaded hole Chassis
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: Between 0.140 inches and 0.166 inches Mounting Method: Unthreaded hole Mounting Type For Which Designed: Chassis
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 14 Polarization Type: Contact position Projection Length Above Mounting Surface: Between 0.140 inches and 0.166 inches Between 0.140 inches and 0.166 inches Mounting Method: Unthreaded hole Mounting Type For Which Designed: Chassis Contact Position Arrangement Style:

Contact surfaces gold and contact surfaces silver



Precious Material And Weight: 0.014 gold grains, troy and 0.014 silver grains, troy **Precious Material:** Gold and silver **Furnished Items And Quantity:** 2 screw and 2 flat washer and 2 nut and 2 stud Terminal Type And Quantity: 14 solder well Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A02300
