

View Online at <https://aerobasegroup.com/nsn/5935-00-627-2438>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape quick connect

Overall Length:

1.343 inches

Overall Width:

0.469 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 military specification single treatment response

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.