

View Online at <https://aerobasegroup.com/nsn/5935-00-629-5937>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape quick connect

**Overall Length:**

1.500 inches

**Overall Width:**

1.077 inches

**Environmental Protection:**

Corrosion resistant

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

C all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thread Size:**

0.750 inches

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends all contact groupings

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

2 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial socket all mating ends all contact groupings

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.