

View Online at <https://aerobasegroup.com/nsn/5935-00-629-5937>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape quick connect

Overall Length:

1.500 inches

Overall Width:

1.077 inches

Environmental Protection:

Corrosion resistant

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

C all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Size:

0.750 inches

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

2 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.